



exalux TAPE10-SMD2110-XXXX-W19-24

SCENIC SERIES



90
CRI

19
W/M

24
VDC

TECHNICAL SPECIFICATIONS

Number Led/M	280
Power W/m	19,0W
PCB Width	10mm
CRI (Ra) min	90-94
Max length(10% voltage drop)	5m
Cut Size	25mm (2700K, 3000K, 4000K, 6000K) 50 mm (2700K-6000K)
Adhésive Tape	3M 9472



P/N	CCT	CRI (Ra)	Power (W/M)	Efficacy LM/W	LM/M	Working voltage	IP Rated
TAPE10-SMD2110-TW2760-W19-24 SKU : FLX.000.021	2700K ± 5% 6000K ± 5%	90-94	19,0 ± 5%	73 ± 5% 89 ± 5%	777 ± 5% 912 ± 5%	24VDC	IP20
TAPE10-SMD2110-K27-W19-24 SKU : on request	2700K ± 5%	90-94	19,0 ± 5%	74 ± 5%	1 463 ± 5%	24VDC	IP20
TAPE10-SMD2110-K30-W19-24 SKU : FLX.000.023	3000K ± 5%	90-94	19,0 ± 5%	82 ± 5%	1 649 ± 5%	24VDC	IP20
TAPE10-SMD2110-K40-W19-24 SKU : FLX.000.027	4000K ± 5%	90-94	19,0 ± 5%	87 ± 5%	1 732 ± 5%	24VDC	IP20
TAPE10-SMD2110-K60-W10-24 SKU : on request	6000K ± 5%	90-94	19,0 ± 5%	94 ± 5%	1 829 ± 5%	24VDC	IP20

DIMENSIONS

2700K/3000K/4000K/6000K

TUNABLE WHITE 2700K-6000K

